Specifications





APC Easy UPS On-Line, 15kVA/ 15kW, Rackmount 9U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended Runtime, W/ Rail Kit

SRV15KRILRK

Overview

Lead time	Usually Ships within 4 Weeks	
Main		
Main Input Voltage	230 V AC	
	415 V AC	
Product or component type	Uninterruptible power supply (UPS)	
Other Input Voltage	220 V	
	230 V	
	415 V	
Main Output Voltage	230 V	
Other Output Voltage	220 V	
	240 V	
Rated power in W	15000 W	
Rated power in VA	15000 VA	
Output connector type	Hard wire 3-wire (1P + N + E) 1	
Number of rack unit	9U	
Provided equipment	1 USB cable	
	1 RS-232 configuration cable	
	3 rack mounting brackets	
	3 stabilization/wall mounting feet	
	6 jumper bar	
	2 external battery pack 1 battery cable	
	user manual	
Banga of product		
Range of product	Easy UPS On-Line	

Batteries & Runtime

Run Time	View Runtime Graph	
Efficiency	View Efficiency Graph 🖸	
Battery type	Lead-acid battery	
Battery voltage	+/- 120 V	
Extended runtime	1	
Number of battery filled slots	0	
Number of battery free slots	0	
Battery recharge time	6 h	
Battery charger power	2340 W rated	

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

General

Redundant

Physical

5		
Colour	Black (RAL 7010)	
Height	39.3 cm	
Width	43.8 cm	
Depth	69.0 cm	
Net weight	157 kg	
Mounting location	Front	
Mounting preference	No preference	
Mounting mode	Rack-mounted	
USB compatible	Yes	
Mounting position	Horizontal	

Input

Input voltage limits	110300 V half load 176300 V full load
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Network frequency	4070 Hz auto sensing

Output

Maximum configurable power in VA	15000 VA	
Maximum configurable power in W	15000 W	
Output frequency	50/60 Hz +/- 3 Hz sync to mains	
Harmonic distortion	2 %	
UPS type	Double conversion online	
Wave type	Sine wave	
Efficiency	95 % (full load)	
Additional information	Configurable for 220 : 230 or 240 nominal output voltage	
Bypass type	Internal bypass (automatic and manual)	
Crest factor	3:1	

Conformance

Product certifications	CE UKCA
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing

Operating altitude	03000 m	
Ambient air temperature for storage	-2060 °C	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	015000 m	
Acoustic level	65 dBA	
Heat dissipation	2503 Btu/h	
IP degree of protection	IP20	

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm	
Emergency power off Yes		
control panel	Multifunction LCD status and control console	

Surge Protection and Filtering

Surge energy rate	600 J
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1000 mm
Package 1 Width	900 mm
Package 1 Length	600 mm
Package 1 Weight	196 kg

Contractual warranty

Warranty

2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Q	Environmental footprint	
Q	Environmental footprint	

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins